

Mikoterm

Tehničke karakteristike blok kotlova serije COMPACT 6-18 kW donji izvod					
COMPACT 6-18kW	Jed.mere	C 06	C 09	C 12	C 18
Snaga	kW	6	9	12	18
Gr.grupe	kW	6	4,5 + 4,5	6 + 6	9 + 9
Dimenzije	mm	750x370x180	750x370x180	750x370x180	750x370x180
Priključak	col	1	1	1	1
Zapremina kotla	lit.	13	13	13	13
Zapremina ekspanzione posude	lit.	8	8	8	8
Maksimalni radni pritisak	bar	3	3	3	3
Napojni vod	mm ²	5x2,5	5x2,5	5x4	5x6
Osigurači	A	3x16	3x20	3x25	3x35

Tehničke karakteristike blok kotlova serije COMPACT 6-24 kW gornji izvod						
COMPACT 6-24kW	Jedinica mere	C 06	C 09	C 12	C 18	C 24
Snaga	kW	6	9	12	18	24
Gr.grupe	kW	6	4,5 + 4,5	6 + 6	9 + 9	12 + 6 + 6
Dimenzije	mm	710x370x180	710x370x180	710x370x180	710x370x180	710x540x180
Priključak	col	1	1	1	1	1
Zapremina kotla	lit.	13	13	13	13	20
Zapremina ekspanzione posude	lit.	8	8	8	8	15
Maksimalni radni pritisak	bar	3	3	3	3	3
Napojni vod	mm ²	5x2,5	5x2,5	5x4	5x6	5x6
Osigurači	A	3x16	3x20	3x25	3x35	3x50



Tehničke karakteristike podnih kotlova								
TK-24	Jedinica mere	TK-24 24	TK-24 30	TK-24 36	TK-24 42	TK-24 45	TK-24 50	TK-24 60
Snaga	kW	24	30	36	42	45	50	60
Gr.grupe	kW	12 + 6 + 6	12 + 12 + 6	12 + 12 + 12	18 + 15 + 9	18 + 18 + 9	20 + 20 + 10	20 + 20 + 20
Dimenzije	mm	620x510x200	650x400x400	650x400x400	850x400x400	850x400x400	850x400x400	850x400x400
Priključak	col	5/4	6/4	6/4	6/4	6/4	6/4	6/4
Zapremina kotla	lit.	22	34	34	54	54	54	54
Maksimalni radni pritisak	bar	3	3	3	3	3	3	3
Napojni vod	mm ²	5x6	5x10	5x10	5x16	5x25	5x25	5x35
Osigurači	A	3x50	3x50	3x63	3x80	3x100	3x100	3x100

Tehničke karakteristike zidnih kotlova						
TK-24	Jedinica mere	TK-24 06	TK-24 09	TK-24 12	TK-24 18	TK-24 24
Snaga	kW	6	9	12	18	24
Gr.grupe	kW	On/off	4,5+4,5	6+6	6+6+6	6+9+9
Dimenzije	mm	550x310x100	550x310x100	550x310x100	630x380x190	630x380x190
Priključak	col	1	1	1	1	1
Zapremina suda	lit.	8	8	8	22	22
Maksimalni radni pritisak	bar	3	3	3	3	3
Napojni vod	mm ²	5x2,5	5x2,5	5x4	5x6	5x6
Osigurači	A	3x16	3x20	3x25	3x35	3x50